




IT'S ONE THING TO MANUFACTURE GUNS AND ANOTHER TO LIVE AND BREATHE THEM.

The Barrett® name has become synonymous with precision long range, large-caliber firearms. From humble beginnings, to now having products used by 78 State Department approved countries, Barrett is also the first father/son team to have each designed a rifle that was adopted by the U.S. Military. The legacy continues as it has for over the last 40 years by meticulously designing, innovating, and manufacturing the most highly sought after rifles in the world.

«

# THE LINEUP






























# M107A1<sup>m</sup>

### **DRIVEN TO GO FURTHER.**

What happens when you combine 40 years of research and development with feedback from the most demanding military end users? You get the M107A1. While it may share the same iconic look and legendary reliability of legacy Barrett firearms, that is where the similarities end.

Utilizing state-of-the-art design, manufacturing, and materials, every component of the rifle has been engineered to be lighter and stronger than its predecessors. In addition to a 4-pound weight reduction, the M107A1 is optimized for use with a sound suppressor, providing a much-needed signature reduction capability to the warfighter. Lighter, stronger, more precise, and more capable; the M107A1 has truly been engineered for performance.



COMES WITH: 10-round magazine, bipod, monopod, and hard carrying case.



### **FEATURES**

- Recoil-operated, semi-automatic
- Suppressor-ready bolt carrier and buffer assemblies
- Accepts Barrett QDL Suppressor
- 4 lbs. (1.8 kg) overall weight reduction compared to original M107
- 5 | Electroless nickel plating on bolt assembly for reduced wear, maintenance, and added corrosion resistance
- Lightweight aluminum upper receiver with integral 23" (584 mm) 27 MOA M1913 optics rail
- 20" (508 mm)\* or 29" (737 mm) barrel with chrome-lined chamber and bore
- Mil-Spec hard anodized base with Cerakote™ Black, Tungsten Grey, or Flat Dark Earth final finish for enhanced corrosion resistance
- 10-round steel magazine with cartridge witness indicators
- 10 | Flip-up iron sights
- 11 | Modular rear hand grip mounted on M1913 rail accepts lightweight adjustable monopod
- 12 | Lightweight adjustable bipod
- 13 | Thermal cheekpiece
- 14 | Recoil pad
- 15 | Accepts side accessory rails
- 16 | Front and rear sling loops

Caliber	50 BMG	50 BMG
Operation	Recoil-Operated, Semi-Automatic	Recoil-Operated, Semi-Automatic
Barrel Length	20" (508 mm)	29" (737 mm)
Rail	23" / 27 MOA (584 mm)	23" / 27 MOA (584 mm)
Overall Length	48" (1219 mm)	57" (1448 mm)
Twist Rate	1 : 15" (381 mm)	1 : 15" (381 mm)
Weight	27.4 lbs (12.4 kg)	28.7 lbs (13.0 kg)
Mag. Capacity	10	10



# OFTEN IMITATED, NEVER DUPLICATED.

The Model 82A1 is where the Barrett legacy began. Engineered as the first shoulder-fired semi-automatic 50 BMG rifle, the Model 82A1 has been proven in combat in every environment, from snow-covered mountains to wind swept deserts and everything in between. More than just a rifle, the Model 82A1 is an American icon.



# MODEL 82A1<sup>®</sup>



Earth

**COMES WITH:** 10-round magazine, carry handle, bipod, monopod, and hard carrying case.

**AVAILABLE COLORS:** 

Manganese Flat Dark

Manganese Phosphate



### **FEATURES**

- 1 | Recoil-operated, semi-automatic
- 2 High-efficiency arrowhead 2-port brake for 50 BMG and cylindrical 3-port brake for 416 Barrett
- 3 | Steel receivers come with a Mil-Spec phosphate coating for enhanced corrosion resistance
- 4 | 23" (584 mm) 27 MOA M1913 optics rail with carrying handle
- 5 | 20" (508 mm) or 29" (737 mm) barrel with chrome-lined chamber and bore
- 6 10-round steel magazine
- 7 | Flip-up iron sights
- 8 | Rear hand grip accepts adjustable monopod
- 9 | Adjustable bipod
- 10 | Recoil pad
- 11 | Accepts side accessory rails
- 12 | Front and rear sling loops

Caliber	50 BMG	50 BMG	416 Barrett
Operation	Recoil-Operated, Semi-Automatic	Recoil-Operated, Semi-Automatic	Recoil-Operated, Semi-Automatic
Barrel Length	20" (508 mm)	29" (737 mm)	29" (737 mm)
Rail	23" / 27 MOA (584 mm)	23" / 27 MOA (584 mm)	23" / 27 MOA (584 mm)
Overall Length	48" (1219 mm)	57" (1448 mm)	57" (1448 mm)
Twist Rate	1:15" (381 mm)	1 : 15" (381 mm)	1:12" (305 mm)
Weight	30.1 lbs (13.7 kg)	31.4 lbs (14.2 kg)	31.9 lbs (14.5 kg)
Mag. Capacity	10	10	10





### **FULLY LOADED.**

The bolt-action Model 95 represents the ideal balance of size and performance. Its innovative bullpup design minimizes overall length without sacrificing the ballistic performance or precision of the proven 50 BMG cartridge. Fed from a 5-round detachable box magazine, the combat-proven Model 95 is the pinnacle of simplicity for end users who demand precision, reliability, and power on the range or in the fight.





**COMES WITH:** 5-round magazine, bipod, and hard carrying case.

**AVAILABLE COLOR:** 

Manganese Phosphate



### **FEATURES**

- 1 | Compact, lightweight bullpup design
- 2 | Quick takedown bolt carrier assembly with quick release lever
- 3 | Ergonomic bolt handle design
- 4 | Mil-Spec phosphate coated for enhanced corrosion resistance
- 5 | 11.75" (299 mm) 27 MOA M1913 optics rail
- 6 Match-grade 29" (736 mm) fluted barrel with Chrome-lined chamber
- 7 | 3-port high-efficiency muzzle brake
- 8 | 5-round steel magazine
- 9 | Accepts rear adjustable monopod
- 10 | Recoil pad
- 11 | Adjustable bipod

Caliber	50 BMG
Operation	Bolt-Action Repeater
Barrel Length	29" (737 mm)
Rail	11.75" / 27 MOA (299 mm)
Overall Length	45" (1143 mm)
Twist Rate	1:15" (381 mm)
Weight	23.5 lbs (10.7 kg)
Mag. Capacity	5



### RUGGED. RELIABLE. **UNCOMPLICATED.**

The Model 99 is designed for one thing only: to get the job done. With its brilliantly simple design, hard-core construction, and surprisingly few moving parts, it offers match-winning precision time and time again.





**COMES WITH:** A bipod and hard carrying case.

AVAILABLE COLORS:



Black

Flat Dark Earth



### **FEATURES**

- 1 | One piece aluminum extrusion receiver
- 2 | Easy feed, single-shot
- 3 | Interrupted, buttress-threaded bolt for superior lock up
- 4 | Black Mil-Spec hardcoat anodized base with Cerakote™ finish
- 5 | 13.75" (349 mm) 27 MOA attached M1913 optics rail
- 6 | Match grade 29" (736 mm) fluted or 32" (813 mm) heavy barrel with Chrome-lined chamber (416 Barrett only)
- 7 | Available in 50 BMG or 416 Barrett
- 8 | 3-port high-efficiency muzzle brake
- 9 | Rear hand grip accepts adjustable monopod
- 10 | Recoil pad
- 11 | Adjustable bipod

Caliber	50 BMG	50 BMG	416 Barrett
Operation	Single-Shot, Bolt-Action	Single-Shot, Bolt-Action	Single-Shot, Bolt-Action
Barrel Length	29" Fluted (737 mm)	32" Heavy (813 mm)	32" Heavy (813 mm)
Rail	13.75" / 27 MOA (349 mm)	13.75" / 27 MOA (349 mm)	13.75" / 27 MOA (349 mm)
Overall Length	47" (1194 mm)	50" (1270 mm)	50" (1270 mm)
Twist Rate	1:15" (381 mm)	1 : 15" (381 mm)	1 : 12" (305 mm)
Weight	23 lbs (10.4 kg)	25 lbs (11.3 kg)	25 lbs (11.3 kg)
Shot Capacity	1	1	1



### **RESILIENT AND PRECISE.**

The MRAD® adapts to a variety of needs without sacrificing performance. This bolt-action system continues to define a new class of long-range precision rifles available in 7 user-changeable calibers.





MRAD



**COMES WITH:** (2) 10-round magazines, (2) sling swivels, (3) accessory rails, and hard carrying case.

AVAILABLE COLORS:

Black

Tungsten Grey

Flat Dark Earth




### **FEATURES**

- 1| Push button adjustable length of pull and recoil pad height
- 2 | Polymer cheek piece is height adjustable and reversible
- 3 | Lightweight folding stock provides compact mobility
- 4 | Polymer bolt guide acts as dust cover and provides smooth bolt cycling
- 5 | 10 MIL rail
- 6 | Mil-Spec hard anodized base with Cerakote™ Black, Tungsten Grey, or Flat Dark Earth final finish
- 7 | M-LOK® compatible upper receiver
- 8 | Match-grade, fluted stainless steel barrels
- 9 | High-efficiency, suppressor-capable muzzle brake
- 10 | 7 user changeable calibers
- 11 | Relief cut magazine well for quick reloads
- 12 | 10-round, drop free, polymer magazine
- 13  $\mid$  Ambidextrous magazine release is accessible while maintaining firing grip
- 14 Oversized trigger guard allows access with gloves
- 15 | Adjustable 2-stage trigger module can be removed without tools
- 16 | Accepts most standard M4/M16 pistol grips
- 17 | Thumb-operated 45° safety configurable for right / left-handed operation
- 18 | Recoil pad with push button height adjustment
- 19 | 5 Shot, Sub-MOA Performance
- 20 | Accepts 5-slot M-LOK® rails and 9-slot M-LOK® rails

Caliber	338 LM	338 NM	300 NM	300 PRC	300 WM	308 Win	6.5 Creed
Operation	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action
	Repeater	Repeater	Repeater	Repeater	Repeater	Repeater	Repeater
Barrel	26"	26"	26"	26"	26"	17" / 24"	24"
Length	(660 mm)	(432/610mm)	(610 mm)				
Rail	22" / 10 Mil	22" / 10 Mil					
	(559 mm)	(559 mm)					
Overall	49.4"	49.4"	49.4"	49.4"	49.4"	40.4" / 47.4"	47.4"
Length	(1255 mm)	(1026/1204mm)	(1204 mm)				
Twist	1: 9.4"	1 : 9.4"	1 : 8"	1 : 8"	1 : 8"	1 : 8"	1 : 8"
Rate	(240 mm)	(240 mm)	(200 mm)	(200 mm)	(200 mm)	(200 mm)	(200 mm)
Weight	14.5 lbs	11.9 / 13.3 lbs	13.3 lbs				
	(6.6 kg)	(5.4 / 6.0 kg)	(6.0 kg)				
Mag. Capacity	10	10	10	10	10	10	10









# MRAD<sup>®</sup> SMR

### DISTINCT BY DESIGN.

The MRAD® SMR (Single Mission Rifle) is a fixed-caliber and non-folding stock rifle system built with a specific purpose in mind. The simplified package retains 90% parts commonality with the standard MRAD, and offers the user a choice between the 7 non-interchangeable calibers.\*

\* The MRAD SMR does not accept MRAD Barrel conversion kits



**COMES WITH:** 10-round magazine, accessory rail, and box with custom foam.

AVAILABLE COLORS:

Black

Tungsten Grey Flat Dark Earth



### **FEATURES**

- 1 | Polymer cheek piece is height adjustable and reversible
- 2 | Fixed Stock (Additional Length of Pull available with Spacer Kit)
- 3 Polymer bolt guide acts as dust cover and provides smooth bolt cycling
- 4 | 10 MIL rail
- 5 | Mil-Spec hard anodized base with Cerakote™ Black, Tungsten Grey, or Flat Dark Earth final finish
- 6 | M-LOK® compatible upper receiver
- 7 | High-efficiency, suppresso- capable muzzle brake
- 8 7 non-interchangeable calibers
- 9 | Match-grade, fluted stainless steel barrels
- 10 | Beveled magazine well for quick reloads
- 11 | 10-round, drop-free, polymer magazine
- 12 | Ambidextrous magazine release is accessible while maintaining firing grip
- 13 | Oversized trigger guard allows access with gloves
- 14 | Adjustable 2-stage trigger module can be removed without tools
- 15 | Accepts most standard M4/M16 pistol grips
- 16 | Thumb-operated 45° safety configurable for right / left-handed operation
- 17 | Non-adjustable recoil pad
- 18 | 5-Shot, Sub-MOA Performance
- 18 7-slot M-LOK® rail

### **SPECIFICATIONS**

Caliber	338 LM	338 NM	300 NM	300 PRC	300 WM	308 Win	6.5 Creed
Operation	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action	Bolt-Action
	Repeater	Repeater	Repeater	Repeater	Repeater	Repeater	Repeater
Barrel	26"	26"	26"	26"	26"	17" / 24"	24"
Length	(660 mm)	(432/610mm)	(610 mm)				
Rail	22" / 10 Mil	22" / 10 Mil					
	(559 mm)	(559 mm)					
Overall	48.5"	48.5"	48.5"	48.5"	48.5"	39.5"/46.5"	46.5"
Length	(1232 mm)	(1003/1181mm)	(1181mm)				
Twist	1: 9.4"	1 : 9.4"	1 : 8"	1 : 8"	1 : 8"	1:8"	1 : 8"
Rate	(240 mm)	(240 mm)	(200 mm)	(200 mm)	(200 mm)	(200 mm)	(200 mm)
Weight	12.3 lbs	10.6 / 12.0 lbs	12.0 lbs				
	(5.6 kg)	(4.8 / 5.4 kg)	(5.4 kg)				
Mag. Capacity	10	10	10	10	10	10	10

\_\_



### **TACTICALLY PROVEN.**

As the USSOCOM and U.S. Army contract winner, the MK22™ is an elite configuration of the MRAD chambered in 300 NM, with the complete kit including conversions to 338 NM and 7.62x51 NATO.





**GOMES WITH:** (2) 10-round magazines, bipod, bag rider, (2) sling swivels, (3) accessory rails, ASR or PSR scope & mount\*, factory zeroing target, and hard carrying case.

AVAILABLE COLOR:

Coyote

\*When purchased as scope combo kit



### **FEATURES**

- 1 | Push button adjustable length of pull and recoil pad height
- 2 | Polymer cheek piece is height adjustable and reversible
- 3 Lightweight folding stock provides compact mobility
- 4 Polymer bolt guide acts as dust cover and provides smooth bolt cycling
- 5 10 MIL rail
- 6 | Mil-Spec hard anodized base with Cerakote™ Coyote final finish
- 7 M-LOK® compatible upper receiver
- 8 | Match-grade, fluted stainless steel barrels
- 9 | High-efficiency, suppressor-capable muzzle brake
- 10 | 3 user-changeable calibers
- 11 | Beveled magazine well for quick reloads
- 12 | 10-round, drop free, polymer magazine
- 13 | Ambidextrous magazine release is accessible while maintaining firing grip
- 14 | Oversized trigger guard allows access with gloves
- 15 | Factory set 2.5 lb. single-stage trigger with anti-tamper epoxy on the adjustment screws
- 16 | Accepts most standard M4/M16 pistol grips
- 17 | Thumb-operated 45° safety configurable for right / left-handed operation
- 18 | Bag rider rail cover
- 19 | 9-slot M-LOK® rails
- 20 AML 338 Suppressor sold separately

Operation   Bolt-Action Repeater   Bolt-Action Repeater   Bolt-Action Repeater     Barrel Length   27" (686 mm)   26" (660 mm)   20" (508 mm)     Rail   22" / 10 Mil (559 mm)   22" / 10 Mil (559 mm)   (559 mm)     Overall Length   49.4" (1255 mm)   48.4" (1229 mm)   42.4" (1077 mm)     Twist Rate   1: 9.4" (240 mm)   1: 8" (200 mm)   1: 8" (200 mm)     Weight   15.2 lbs (7.0 kg)   15.2 lbs (7.0 kg)   13.9 lbs (6.3 kg)     Mag. Capacity   10   10   10	Caliber	338 NM	300 NM	7.62 x 51 NATO
Rail 22" / 10 Mil (559 mm) 22" / 10 Mil (559 mm) 22" / 10 Mil (559 mm)   Overall Length 49.4" (1255 mm) 48.4" (1229 mm) 42.4" (1077 mm)   Twist Rate 1: 9.4" (240 mm) 1: 8" (200 mm) 1: 8" (200 mm)   Weight 15.2 lbs (7.0 kg) 15.2 lbs (7.0 kg) 13.9 lbs (6.3 kg)	Operation	Bolt-Action Repeater	Bolt-Action Repeater	Bolt-Action Repeater
Weight (559 mm) (559 mm) (559 mm)   1:9.4" (1255 mm) 48.4" (1229 mm) 42.4" (1077 mm)   1:8" (200 mm) 1:8" (200 mm) 1:8" (200 mm)   Weight 15.2 lbs (7.0 kg) 15.2 lbs (7.0 kg) 13.9 lbs (6.3 kg)	Barrel Length	27" (686 mm)	26" (660 mm)	20" (508 mm)
Twist Rate 1: 9.4" (240 mm) 1: 8" (200 mm) 1: 8" (200 mm)   Weight 15.2 lbs (7.0 kg) 15.2 lbs (7.0 kg) 13.9 lbs (6.3 kg)	Rail			
Weight 15.2 lbs (7.0 kg) 15.2 lbs (7.0 kg) 13.9 lbs (6.3 kg)	Overall Length	49.4" (1255 mm)	48.4" (1229 mm)	42.4" (1077 mm)
	Twist Rate	1: 9.4" (240 mm)	1:8" (200 mm)	1: 8" (200 mm)
Mag. Capacity 10 10 10	Weight	15.2 lbs (7.0 kg)	15.2 lbs (7.0 kg)	13.9 lbs (6.3 kg)
	Mag. Capacity	10	10	10





# SUPPRESSORS

## AM & AML

Adapter-Mount (AM) and Adapter Mount Locking (AML) monocore suppressors are specifically designed for precision bolt-action rifles resulting in minimal point impact shift. The AM 338 and AML 338 can also be mounted to a variety of calibers using one of the following Barrett® AM 338

Muzzle Brake Adapters: 5/8 x 24 and 3/4 x 24.







**AVAILABLE COLORS:** 

Black AM 30 / AM 338 Coyote AML 338

Model	AM30	AM338	AML338
Rated	308 Win and below	338 LM/NM and below	338 LM/NM and below
Length	8.3" (211 mm)	9.9" (252 mm)	10.3" (262 mm)
Diameter	1.5" (38 mm)	1.8" (46 mm)	1.9" (48 mm)
Weight	.775 lbs (0.4 kg)	1.3 lbs (0.6 kg)	1.6 lbs (0.7 kg)
Sound Reduction	< 135 db	< 140 db	< 140 db
Mount & Thread Pitch	Barrett® AM 30 Muzzle Brake Adapter: 5/8 x 24	Barrett® AM 338 Muzzle Brake Adapter: 3/4 x 24	Barrett® AM 338 Muzzle Brake Adapter: 3/4 x 24
Materials	Grade 5 Titanium Core	Grade 5 Titanium Core	Grade 5 Titanium Core with 4140 Lock Ring



**COMES WITH:** A MOLLE carrying case and a mirage mitigating cover.



**AVAILABLE COLORS:** 

Black

Flat Dark Earth



Model	QDL (Quick Detach Large)
Caliber	50
Length	14.8" (376 mm)
Diameter	2.5" (64 mm)
Weight	4.9 lbs (2.2 kg)
Sound Reduction	23 dB
Mount / Thread Pitch	Barrett® QDL Muzzle Brake / 7/8 x 14
Materials	4130 Steel









# AMMUNITION

«

# **AMMUNITION**





Caliber	50 BMG
Cartridge Quantity	10 Rounds (Box) / 250 Rounds (Case)
Overall Length	5.450" (140 mm)
Muzzle Velocity	2,800 fps (29" Barrel)
Bullet / Weight	M-33 / 661 gr
Ballistic Coefficient	0.62 (G1)



### **SPECIFICATIONS**

Caliber	416 Barrett
Cartridge Quantity	10 Rounds (Box) / 80 Rounds (Case)
Overall Length	4.650" (119 mm)
Muzzle Velocity	3,005 fps (32" Barrel)
Bullet / Weight	Cutting Edge Bullets MTAC / 452 gr
Ballistic Coefficient	0.83 (G1), 0.42 (G7)

<<



# ZERO-GAP® RINGS

## **ZERO-GAP® RINGS**



Black










### **SPECIFICATIONS**

Weight	8.3 oz (235.3 g), 8.5 oz (241.0 g)
Size	30 mm, 34 mm, and 35 mm
Base Type	MIL-STD-1913 Rail
Ring Width	1.2" (31 mm)
Surface Gripping Area	8.2 inch <sup>2</sup>
Material	7075 T6 Aluminum
Finish	Hard Anodized Black
Height	1.3" - 1.4" (33 mm - 36 mm)

### **HEIGHTS**

1.400



### HIGH 30 mm

Up to 50 mm objective with lens cover and extended scope rail.



### **ULTRA HIGH**

objective with lens cover and extended scope rail.



### **ULTRA HIGH** 34 mm

Up to 56 mm objective with lens cover and extended scope rail.



### **ULTRA HIGH** 35 mm

Up to 56 mm objective with lens cover and extended scope rail.



«



### **BARRETT FIREARMS HEADQUARTERS**

P.O. Box 1077 Murfreesboro, TN 37133 USA 615-896-2938

#### **SALES & CUSTOMER SERVICE**

mail@barrett.net

#### **TRAINING**

training@barrett.net

### **LAW ENFORCEMENT**

le@barrett.net

#### **MILITARY**

military@barrett.net

#### **DEALER DIRECT**

dealer@barrett.net

#### **MARKETING & MEDIA**

media@barrett.net

#### INTERNATIONAL

international@barrett.net

© 2023 BARRETT / ALL RIGHTS RESERVED

